


OFI 202-40B (oil-less)

Voltage	V	200	200	230	240	3x400	3x440						
Frequency	Hz	50	60	50	60	50	60						
Motor	HP	2.00	2.00	2.00	2.00	2.00	2.00						
	kW	1.47	1.47	1.47	1.47	1.47	1.47						
Displacement	l/min	290	328	290	328	290	328						
	CFM	10.24	11.58	10.24	11.58	10.24	11.58						
FAD @ 8 bar	l/min	130	146	130	146	130	146						
	CFM	4.59	5.16	4.59	5.16	4.59	5.16						
Max. pressure ¹⁾	bar	8	8	8	8	8	8						
	psi	120	120	120	120	120	120						
Max. current	A	-	-	8.0	9.0	5.0	5.0						
Tank size	litres	40	40	40	40	40	40						
	gallon	10.6	10.6	10.6	10.6	10.6	10.6						
Weight	kg	59	59	59	59	59	59						
	lbs	130	130	130	130	130	130						
Noise level	dB(A)/1m	76	79	76	79	76	79						
Thermal protection		Yes	Yes	Yes	Yes	Yes	Yes						
Duty cycle		100%	100%	100%	100%	100%	100%						



Dimensions (l x w x h)
556 x 442 x 677 mm / 21 7/8 x 17 3/8 x 26 5/8 inch

¹⁾ Higher pressure available upon request

Technical modifications reserved



JUN-AIR®

E-mail: info@jun-air.dk
Internet: www.jun-air.com