

**NEW!**  
WITH 9 LITER ROTOR



# Aliva<sup>®</sup>-257 concrete spraying machine

## THE ALL-ROUNDER

### ■ Usable in many different application fields

The versatile Aliva<sup>®</sup>-257 works as efficiently on small renovations as it does on excavation support or in mining.

### ■ For dry and wet shotcrete

With this very robust and compact rotary shotcrete machine you can spray dry or wet mixes thanks to its special machine design and versatility in the thin-stream process. For dry spraying with minimum wear we especially recommend the Aliva<sup>®</sup>-257 with the new rubber sealing plates.

### ■ Incredible output capacity range

Available with 3 rotor sizes the Aliva<sup>®</sup>-257 reaches flow rates from 0.7 up to 9.6 m<sup>3</sup>/h.

**aliva**<sup>®</sup>

**BUILDING TRUST**



# Aliva®-257

## VERSATILE CONCRETE SPRAYING MACHINE

The most versatile Aliva rotary machine for concrete spraying is the Aliva®-257!

Whether you need to process dry or wet mixes in high or small volumes, with the Aliva®-257 you can do it. In addition to the very robust steel sealing plates we now offer the Aliva®-257 with rubber sealing plates. Especially for dry mixes we recommend the rubber sealing plates for low-wear concrete spraying. Economical spraying operation without long standstill times and with lowest wear costs is now possible, thanks to the reliable Aliva® machine quality and premium original Aliva® spare parts.

### ADVANTAGES AND BENEFITS

- Theoretical output from 0.7 up to 9.6 m<sup>3</sup>/h
- Easily overcome obstacles of long or high conveying distances (dry mix)
- Less dust development
- Reduced rebound
- For concrete repair, slope stabilization, excavation support or in mining
- Light and compact machine design
- Stepless adjustment of conveying capacity

### STANDARD CONFIGURATION

- Rotor chamber ventilation
- Automatic lubrication system
- Frequency convertor
- Vibrating hopper

### OPTIONS

- Aliva® accessory kit rubber sealing plates (for machines already in use)
- Original Aliva® accessories e.g. Converto nozzles and Aliva® original conveying hoses

### Technical data

Machine type	Process	Variants / Drive	Operating voltage / air consumption motor	Rotor size in liters	Theoretical Output in m <sup>3</sup> /h*	Recommended hose sizes	Grain sizes in mm	Max. Conveying distance in m horizontal/vertical	Weight in kg	Dimensions in mm	
rotary machine, Aliva® -257	thin-stream process, for dry and wet shotcrete	TOP: Electric	3 x 380 - 480 V 50 - 60 Hz	2.5	0.7 - 2.0	DN 38	12	Dry: 300/100	650	Length	1'579
				6.0	1.9 - 5.0	DN 50	16			Height	1'321
		AIR: Air	7 Nm <sup>3</sup> /min. with 5 bar	9.0	3.6 - 9.6	DN 60	20	Wet: 40/15		Width	800

\* For a theoretical filling level of 100%. Prior to use or processing, always consult the current product data sheet of the products used. The current version of our respective General Terms and Conditions applies.

### Aliva®-257 in operation



### Rubber and steel sealing plates



### SIKA SCHWEIZ AG

Aliva Equipment  
Tüffenwies 16  
CH-8048 Zürich  
Switzerland

### Contact

Phone +41 58 436 32 22  
Fax +41 58 436 41 40  
www.aliva-equipment.com  
aliva.equipment@ch.sika.com



BUILDING TRUST

